

One piece fixing Tie with Fir Tree, with Disc



One piece fixing Tie with Fir Tree, with Disc		standard								Indoor use		Operating Temperature: -40°C~+85°C		
Product code	Bundle Ø (mm)		Size (mm)						Max. Panel Thickness (mm)	Hole Ø (mm)	Min. loop Tensile Strength N (kgf)	Packing		
	Min.	Max	L	A	B	Ø D	G	T				(pcs/bag)	(pcs/case)	
QX170-FT7	1.6	30	170	5.3	15.5	16	9.9	1.4	4.5	6.8-7.2	147(14.99)	100	2500	
QX170-FT7-LH	1.6	30	170	5.3	16.6	16	9.6	1.4	4.5	6.8-7.2	147(14.99)	100	2500	
QX30SDP6	1.5	31	170	5	—	22	12.5	1.5	7.0	6.3-7.1	135(13.77)	100	2000	



One piece fixing Tie with Fir Tree, with Disc		Heating Resistant								High Temperature		Operating Temperature: -40°C~+105°C		
Product code	Bundle Ø (mm)		Size (mm)						Max. Panel Thickness (mm)	Hole Ø (mm)	Min. loop Tensile Strength N (kgf)	Packing		
	Min.	Max	L	A	B	Ø D	G	T				(pcs/bag)	(pcs/case)	
QX170-FT7-HS	1.6	30	170	5.3	15.5	16	9.9	1.4	4.5	6.8-7.2	147(14.99)	100	2500	



One piece fixing Tie with Fir Tree, with Disc		Heating and Weather Resistant								High Temperature and outdoor		Operating Temperature: -40°C~+105°C		
Product code	Bundle Ø (mm)		Size (mm)						Max. Panel Thickness (mm)	Hole Ø (mm)	Min. loop Tensile Strength N (kgf)	Packing		
	Min.	Max	L	A	B	Ø D	G	T				(pcs/bag)	(pcs/case)	
QX160-FT5-HSW	3	30	163	4	11.4	13	5.6	1.4	3.2	4.5-5.0	100 (10.20)	100	2500	