

Screw Mount Cable Clamps

Characteristics

- Screw mount cable clamps are designed to hold cables, tubes, and components in domestic appliance, electronics and electric apparatus generally.
- Good temperature resistance as well as offering high strength. A feature of the cable clamps are their versatility to accept cables of differing sizes through the use of a range of fixing holes – this feature enables users to minimize stock holding of a large range of clamps.
- Light weight makes them particularly suitable for use in areas such as aircraft and aerospace where minimizing weight, but retaining a strong fixing, is vitally important.

Technical information

- Material - UL Approved Polyamide 6.6,
- Temperature range: -20°C to +85°C (-4°F to 185°F)
- Color: Natural, Black
- Flammability rating: UL 94V-2



Product code	Mounting Hole Centers(A)		Width (W)		Thickness (T)		Max BundleΦ		Mounting HoleΦ mm(inch)	Pack quantity [pcs]
	[mm]	[in]	[mm]	[in]	[mm]	[in]	[mm]	[in]		
GCL-1/8S	8.2	0.32	9.1	0.36	1.3	0.05	3.3	0.13	5.5(0.21)	100/1000
GCL-3/16S	9.6	0.38	9.1	0.36	1.3	0.05	4.8	0.19	5.5(0.21)	100/1000
GCL-1/4S	10.3	0.41	9.1	0.36	1.3	0.05	6.6	0.26	5.5(0.21)	100/1000
GCL-5/16S	10.6	0.42	9.1	0.36	1.3	0.05	7.8	0.31	5.5(0.21)	100/1000
GCL-3/8S	11.9	0.47	9.2	0.37	1.3	0.05	9.7	0.38	5.5(0.21)	100/1000
GCL-1/8	9.1	0.36	12.7	0.50	1.5	0.06	2.9	0.11	5.3(0.21)	100/1000
GCL-1/4	11.4	0.45	12.7	0.50	1.5	0.06	5.9	0.23	5.3(0.21)	100/1000
GCL-3/8	13.4	0.53	12.1	0.48	1.5	0.06	9.1	0.36	5.3(0.21)	100/1000
GCL-1/2	15.0	0.59	12.7	0.50	1.5	0.06	12.2	0.48	5.3(0.21)	100/1000
GCL-9/16	15.8	0.62	12.7	0.50	1.5	0.06	13.8	0.54	5.3(0.21)	100/1000
GCL-3/4	19.8	0.78	12.7	0.50	1.5	0.06	18.6	0.73	5.3(0.21)	100/1000
GCL-7/8	21.4	0.84	12.7	0.50	1.5	0.06	21.8	0.86	5.3(0.21)	100/1000
GCL-1-1/8	24.6	0.97	12.7	0.50	1.5	0.06	27.9	1.10	5.3(0.21)	100/1000
GCL-5/16L	10.6	0.42	12.7	0.50	1.3	0.05	7.6	0.30	5.3(0.21)	100/1000

Drawing

