

Corrugated Conduit

- Material: UL approved PA6
- Fireproof: UL94-V0
- Color: Black, other colors are available upon request.
- Operating temperature: -40°C to 125°C , 140°C in short time
- Structure: internal and external are both wave-type.
- Characteristic: Good flexibility, good resistance to distortion and bending, heavy duty; Acid, lubricating oil & coolant liquid resistance, etc. Shiny surface
- Loading Capacity: rub resistance
- Application: Machinery manufacturing, electrical insulation protection, lighting equipment, automobile manufacturing, aviation equipment, subway, train, automatic control and other industries.
- Applying: Insert the wire and cable into the tube and use it with the corresponding type of hose connector.



Specification	Item.No.	Inner diameter x Outer diameter	Curved radius	Std.Pkg
AD13.0	FFP-PP-13.0	10.0 x 13.0	20	100
AD15.8	FFP-PP-15.8	12.0 x 15.8	30	100
AD18.5	FFP-PP-18.5	14.3 x 18.5	40	100
AD21.2	FFP-PP-21.2	17.0 x 21.2	45	100
AD25.0	FFP-PP-25.0	20.0 x 25.0	45	50
AD28.5	FFP-PP-28.5	23.0 x 28.5	50	50
AD31.5	FFP-PP-31.5	26.0 x 31.5	55	50
AD34.5	FFP-PP-34.5	29.0 x 34.5	60	50
AD42.5	FFP-PP-42.5	36.0 x 42.5	70	25
AD54.5	FFP-PP-54.5	48.0 x 54.5	90	25